

GNU Linear Programming Kit

Java Binding

Reference Manual

Version 1.12.0

February 16, 2018

Copyright © 2009-2018 Heinrich Schuchardt, xypron.glpk@gmx.de

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided also that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions.

Windows is a registered trademark of Microsoft Corporation. Java is a registered trademark of Oracle and/or its affiliates. OS X is a trademark of Apple Inc.

Contents

1	Introduction	5
2	Getting started	6
2.1	Installation	6
2.1.1	Windows	6
2.1.2	Linux	7
2.1.3	OS X	9
2.2	Trivial example	10
2.2.1	Windows	10
2.2.2	Linux	11
3	Architecture	12
3.1	GLPK library	12
3.1.1	Source	12
3.1.2	Linux	12
3.1.3	Windows	12
3.2	GLPK for Java JNI library	13
3.2.1	Source	13
3.2.2	Linux	13
3.2.3	Windows	13
3.3	GLPK for Java class library	13
3.3.1	Linux	13
3.3.2	Windows	14
3.3.3	Classpath	14
4	Maven	15
5	Classes	16
6	Usage	18
6.1	Loading the JNI library	18
6.2	Exceptions	19
6.2.1	Implementation details	19
6.3	Network problems	19
6.4	Callbacks	21
6.5	Output listener	23
6.6	Aborting a GLPK library call	23
6.7	Debugging support	23
6.8	Locales	23
6.9	Threads	23
7	Examples	24
7.1	Lp.java	24

7.1.1	Description	24
7.1.2	Coding	24
7.2	Gmpl.java	26
7.2.1	Description	26
7.2.2	Coding	27
8	Troubleshooting	29
9	License	30

Chapter 1

Introduction

The GNU Linear Programming Kit (GLPK)[2] package supplies a solver for large scale linear programming (LP) and mixed integer programming (MIP). The GLPK project is hosted at <http://www.gnu.org/software/glpk>.

It has two mailing lists:

- help-glpk@gnu.org and
- bug-glpk@gnu.org.

To subscribe to one of these lists, please, send an empty mail with a Subject: header line of just "subscribe" to the list.

GLPK provides a library written in C and a standalone solver.

The source code provided at <ftp://gnu.ftp.org/gnu/glpk/> contains the documentation of the library in file doc/glpk.pdf.

The Java platform provides the Java Native Interface (JNI)[3] to integrate non-Java language libraries into Java applications.

Project GLPK for Java delivers a Java Binding for GLPK. It is hosted at <http://glpk-java.sourceforge.net/>.

To report problems and suggestions concerning GLPK for Java, please, send an email to the author at xyprom.glpk@gmx.de.

Chapter 2

Getting started

This chapter will run you through the installation of GLPK for Java and the execution of a trivial example.

2.1 Installation

2.1.1 Windows

The following description assumes:

- You are using a 64-bit version of Windows. Replace folder name w64 by w32 if you are using a 32-bit version.
- The current version of GLPK is 4.65. Please, adjust paths if necessary.
- Your path for program files is "C:\Program Files". Please, adjust paths if necessary.

Download the current version of GLPK for Windows from <https://sourceforge.net/projects/winglpk/>.

The filename for version 4.65 is winglpk-4.65.zip. Unzip the file. Copy folder glpk-4.65 to "C:\Program Files\GLPK\".

To check the installation run the following command:

```
"C:\Program Files\GLPK\w64\glpsol.exe" --version
```

To use GLPK for Java you need a Java development kit to be installed. The Oracle JDK can be downloaded from <http://www.oracle.com/technetwork/java/javase/downloads/index.html>.

To check the installation run the following commands:

```
"%JAVA_HOME%\bin\javac" -version  
java -version
```

2.1.2 Linux

Debian package

For Debian and Ubuntu an installation package for GLPK for Java exists. It can be installed by the following commands:

```
sudo apt-get install libglpk-java
```

The installation will be in /usr not in /usr/local as assumed in the examples below.

Installation from source

Download the current version of GLPK source with

```
wget ftp://ftp.gnu.org/gnu/glpk/glpk-4.65.tar.gz
```

Unzip the archive with:

```
tar -xzf glpk-4.65.tar.gz  
cd glpk-4.65
```

Configure with

```
./configure
```

Make and install with:

```
make  
make check  
sudo make install
```

Check the installation with

```
glpsol --version
```

For the next steps you will need a Java Development Kit (JDK) to be installed.

You can check the correct installation with the following commands:

```
$JAVA_HOME/bin/javac -version  
java -version
```

If the JDK is missing refer to <http://openjdk.java.net/install/> for installation instructions.

To build GLPK for Java you will need package SWIG (Simplified Wrapper and Interface Generator, <http://www.swig.org/>). You can check the installation with the following command:

```
swig -version
```

Most Linux distribution contain a SWIG package. The installation command will depend on the distribution, e.g.

- Debian: sudo apt-get install swig
- Fedora: sudo yum install swig

- Gentoo: sudo emerge swig

Download GLPK for Java from <https://sourceforge.net/projects/glpk-java/files/>.

Unzip the archive with:

```
tar -xzf glpk-java-1.12.0.tar.gz
cd glpk-java-1.12.0
```

Configure with:

```
./configure
```

If configure is called with `--enable-libpath`, class GLPKJN will try to load the GLPK library from the path specified by `java.library.path` (see section 6.1).

Some POSIX systems like OS X have `jni.h` in a special path. You may want to specify this path in the parameters `CPPFLAGS` and `SWIGFLAGS` for the configure script, e.g.

```
./configure \
CPPFLAGS=-I/System/Library/Frameworks/JavaVM.framework/Headers \
SWIGFLAGS=-I/System/Library/Frameworks/JavaVM.framework/Headers
```

If `libglpk.so` is in a special path you may specify this path using parameter `LDLIBRARY`, e.g.

```
./configure LDLIBRARY=-L/opt/lib
```

Make and install with:

```
make
make check
sudo make install
```

If you have no authorization to install GLPK and GLPK for Java in the `/usr` directory, you can alternatively install it in your home directory as is shown in the following listing.

```
# Download source code
mkdir -p /home/$USER/src
cd /home/$USER/src
rm -rf glpk-4.65*
wget http://ftp.gnu.org/gnu/glpk/glpk-4.65.tar.gz
tar -xzf glpk-4.65.tar.gz
rm -rf glpk-java-1.12.0*
wget http://download.sourceforge.net/project/glpk-java/\
glpk-java/glpk-java-1.12.0/libglpk-java-1.12.0.tar.gz
tar -xzf libglpk-java-1.12.0.tar.gz

# Build and install GLPK
cd /home/$USER/src/glpk-4.65
./configure --prefix=/home/$USER/glpk
make
make check
make install

# Build and install GLPK for Java
cd /home/$USER/src/libglpk-java-1.12.0
export CPPFLAGS=-I/home/$USER/glpk/include
```

```

export SWIGFLAGS=-I/home/$USER/glpk/include
export LD_LIBRARY_PATH=/home/$USER/glpk/lib
./configure --prefix=/home/$USER/glpk
make
make check
make install
unset CPPFLAGS
unset SWIGFLAGS

# Build and run example
cd /home/$USER/src/libglpk-java-1.12.0/examples/java
$JAVA_HOME/bin/javac \
-classpath /home/$USER/glpk/share/java/glpk-java-1.12.0.jar \
GmplSwing.java
$JAVA_HOME/bin/java \
-Djava.library.path=/home/$USER/glpk/lib/jni \
-classpath /home/$USER/glpk/share/java/glpk-java-1.12.0.jar:. \
GmplSwing marbles.mod

```

2.1.3 OS X

Installation from source

For building GLPK for Java the package manager Homebrew is needed. The installation and usage is described at <https://brew.sh>.

Install GLPK

```
brew install glpk
```

For the next steps you will need a Java Development Kit (JDK) to be installed.

You can check the correct installation with the following commands:

```
$JAVA_HOME/bin/javac -version
java -version
```

If the JDK is missing it can be installed with

```
brew cask install java
```

To build GLPK for Java you will need package SWIG (Simplified Wrapper and Interface Generator, <http://www.swig.org/>). You can check the installation with the following command:

```
swig -version
```

SWIG can be installed with

```
brew install swig
```

Download GLPK for Java from <https://sourceforge.net/projects/glpk-java/files/>.

Unzip the archive with:

```
tar -xzf glpk-java-1.12.0.tar.gz
cd glpk-java-1.12.0
```

Configure with:

```
./configure
```

If configure is called with `--enable-libpath`, class GLPKJN will try to load the GLPK library from the path specified by `java.library.path` (see section 6.1).

OS X has `jni.h` in a special path. You will have to specify this path by setting parameters `CPPFLAGS` and `SWIGFLAGS` for the configure script.

```
./configure \
CPPFLAGS=-I/System/Library/Frameworks/JavaVM.framework/Headers \
SWIGFLAGS=-I/System/Library/Frameworks/JavaVM.framework/Headers
```

If `libglpk.so` is in a special path you may specify this path using parameter `LDLIBRARY`, e.g.

```
./configure LDLIBRARY=-L/opt/lib
```

Make and install with:

```
make
make check
sudo make install
```

2.2 Trivial example

In the example we will create a Java class which will write the GLPK version to the console.

With a text editor create a text file `Test.java` with the following content:

```
import org.gnu.glpk.GLPK;
public class Test {
    public static void main(String[] args) {
        System.out.println( GLPK.glp_version());
    }
}
```

2.2.1 Windows

Compile the class

```
set CLASSPATH=C:\Program Files\GLPK\glpk-4.65\w64\glpk-java.jar
"%JAVA_HOME%\bin\javac" Test.java
```

Run the class

```
set CLASSPATH=C:\Program Files\GLPK\glpk-4.65\w64\glpk-java.jar;.
java -Djava.library.path="C:\Program Files\GLPK\glpk-4.65\w64" Test
```

The output will be the GLPK version number, for example: 4.65.

2.2.2 Linux

Compile the class

```
javac -classpath /usr/local/share/java/glpk-java.jar Test.java
```

Run the class:

```
java -Djava.library.path=/usr/local/lib/jni \
-classpath /usr/local/share/java/glpk-java.jar:. \
Test
```

The output will be the GLPK version number, for example: 4.65.

Chapter 3

Architecture

A GLPK for Java application will consist of

- the GLPK library
- the GLPK for Java JNI library
- the GLPK for Java class library
- the application code.

3.1 GLPK library

3.1.1 Source

The source code to compile the GLPK library is provided at <ftp://gnu.ftp.org/gnu/glpk/>.

3.1.2 Linux

The GLPK library can be compiled from source code. Follow the instructions in file INSTALL provided in the source distribution. Precompiled packages are available in many Linux distributions.

The usual installation path for the library is /usr/local/lib/libglpk.so.

3.1.3 Windows

The GLPK library can be compiled from source code. The build and make files are in directory w32 for 32 bit Windows and in w64 for 64 bit Windows. The name of the created library is glpk_4_65.dll for revision 4.65.

A precompiled version of GLPK is provided at <http://winglpk.sourceforge.net>.

The library has to be in the search path for binaries. Either copy the library to a directory that is already in the path (e.g. C:\windows\system32) or update the path in the system settings of Windows.

3.2 GLPK for Java JNI library

3.2.1 Source

The source code to compile the GLPK for Java JNI library is provided at <http://glpk-java.sourceforge.net>.

3.2.2 Linux

The GLPK for Java JNI library can be compiled from source code. Follow the instructions in file INSTALL provided in the source distribution.

The usual installation path for the library is /usr/local/lib/libglpk-java.so.

3.2.3 Windows

The GLPK for Java JNI library can be compiled from source code. The build and make files are in directory w32 for 32 bit Windows and in w64 for 64 bit Windows. The name of the created library is glpk_4_65_java.dll for revision 4.65.

A precompiled version of GLPK for Java is provided at <http://winglpk.sourceforge.net>.

The library has to be in the search path for binaries. Either copy the library to a directory that is already in the path (e.g. C:\windows\system32) or update the path in the system settings of Windows.

3.3 GLPK for Java class library

The source code to compile the GLPK for Java class library is provided at <http://glpk-java.sourceforge.net>.

3.3.1 Linux

The GLPK for Java class library can be compiled from source code. Follow the instructions in file INSTALL provided in the source distribution.

The usual installation path for the library is /usr/local/share/java/glpk-java.jar.

For Debian and Ubuntu the following packages are needed for compilation:

- libtool
- swig
- openjdk-6-jdk (or a higher version)

3.3.2 Windows

The GLPK for Java class library can be compiled from source code. The build and make files are in directory w32 for 32 bit Windows and in w64 for 64 bit Windows. The name of the created library is glpk-java.jar.

A precompiled version of GLPK including GLPK-Java is provided at <http://winglpk.sourceforge.net>.

3.3.3 Classpath

The library has to be in the CLASSPATH. Update the classpath in the system settings of Windows or specify the classpath upon invocation of the application, e.g.

```
java -classpath ./glpk-java.jar;.. MyApplication
```

Chapter 4

Maven

For using this library in your Maven project enter the following repository and dependency in your pom.xml:

```
<repositories>
    <repository>
        <id>XypronRelease</id>
        <name>Xypron Release</name>
        <url>https://www.xypron.de/repository</url>
        <layout>default</layout>
    </repository>
</repositories>

<dependencies>
    <dependency>
        <groupId>org.gnu.glpk</groupId>
        <artifactId>glpk-java</artifactId>
        <version>1.12.0</version>
    </dependency>
</dependencies>
```

The artifact does not include the binary libraries, which have to be installed separately.

Chapter 5

Classes

GLPK for Java uses the Simplified Wrapper and Interface Generator (SWIG)[4] to create the JNI interface to GLPK. Classes are created in path org.gnu.glpk.

Class GlpkCallback is called by the MIP solver callback routine.

Interface GlpkCallbackListener can be implemented to register a listener for class GlpkCallback.

Class GlpkTerminal is called by the MIP solver terminal output routine.

Interface GlpkTerminalListener can be implemented to register a listener for class GlpkTerminal.

Class GlpkException is thrown if an error occurs.

Class GLPK maps the functions from glpk.h.

Class GLPKConstants maps the constants from glpk.h to methods.

Class GLPKJNI contains the definitions of the native functions.

The following classes map structures from glpk.h:

- glp_attr
- glp_bfcp
- glp_cpxcp
- glp_iocp
- glp_iptcp
- glp_long
- glp_mpsc
- glp_prob
- glp_smcp
- glp_tran
- glp_tree
- LPXKKT

- `glp_arc`
- `glp_graph`
- `glp_vertex`

The following classes are used to map pointers:

- `SWIGTYPE_p_double`
- `SWIGTYPE_p_f_p_glp_tree_p_void_void`
- `SWIGTYPE_p_f_p_q_const_char_v_____void`
- `SWIGTYPE_p_f_p_void_p_q_const_char_void`
- `SWIGTYPE_p_f_p_void_p_q_void_int`
- `SWIGTYPE_p_int`
- `SWIGTYPE_p_glp_arc`
- `SWIGTYPE_p_glp_graph`
- `SWIGTYPE_p_glp_vertex`
- `SWIGTYPE_p_va_list`
- `SWIGTYPE_p_void`

The following classes are used for network problems:

- `glp_java_arc_data`
- `glp_java_vertex_data`

Chapter 6

Usage

Please, refer to file doc/glpk.pdf of the GLPK source distribution for a detailed description of the methods and constants.

6.1 Loading the JNI library

To be able to use the JNI library in a Java program it has to be loaded. The path to dynamic link libaries can specified on the command line when calling the Java runtime, e.g.

```
java -Djava.library.path=/usr/local/lib/jni/libglpk_java
```

The following code is used in class GLPKJNI to load the JNI library:

```
static {
    try {
        if (System.getProperty("os.name").toLowerCase().contains("windows")) {
            // try to load Windows library
#ifndef GLPKPRELOAD
            try {
                System.loadLibrary("glpk_4_65");
            } catch (UnsatisfiedLinkError e) {
                // The dependent library might be in the OS library search path.
            }
#endif
            System.loadLibrary("glpk_4_65_java");
        } else {
            // try to load Linux library
#ifndef GLPKPRELOAD
            try {
                System.loadLibrary("glpk");
            } catch (UnsatisfiedLinkError e) {
                // The dependent library might be in the OS library search path.
            }
#endif
            System.loadLibrary("glpk_java");
        }
    } catch (UnsatisfiedLinkError e) {
        System.err.println(
            "The dynamic link library for GLPK for Java could not be"
```

```

        + "loaded.\nConsider using\njava-Djava.library.path=");
    throw e;
}
}

```

GLPKPRELOAD is enabled in the Windows build files by default. For POSIX systems it can be enabled by

```
./configure --enable-libpath
```

If the JNI library can not be loaded, you will receive an exception `java.lang.UnsatisfiedLinkError`.

6.2 Exceptions

When illegal parameters are passed to a function of the GLPK native library an exception `GlpkException` is thrown. Due to the architecture of GLPK all GLPK objects are invalid when such an exception has occurred.

6.2.1 Implementation details

GLPK for Java registers a function `glp_java_error_hook()` to `glp_error_hook()` before calling an GLPK API function. If an error occurs function `glp_free_env` is called and a long jump is used to return to the calling environment. Then function `glp_java_throw()` is called which throws `GlpkException`.

6.3 Network problems

For network problems additional data like capacity and cost of arcs or the inflow of vertices has to be specified. The GLPK library does not provide data structures. In GLPK for Java classes `_glp_java_arc_data` and `_glp_java_vertex_data` are provided.

When creating a graph the size of the structures for these classes has to be specified. In some routines the offsets to individual fields in the structures are needed. The following constants have been defined:

- `GLP_JAVA_A_CAP` - offset of field cap in arc data
- `GLP_JAVA_A_COST` - offset of field cost in arc data
- `GLP_JAVA_A_LOW` - offset of field low in arc data
- `GLP_JAVA_A_RC` - offset of field rc in arc data
- `GLP_JAVA_A_X` - offset of field x in arc data
- `GLP_JAVA_A_SIZE` - size of arc data
- `GLP_JAVA_V_CUT` - offset of field cut in vertex data
- `GLP_JAVA_V_PI` - offset of field pi in vertex data
- `GLP_JAVA_V_RHS` - offset of field rhs in vertex data

- GLP_JAVA_V_SET - offset of field set in vertex data
- GLP_JAVA_V_SIZE - size of vertex data

For accessing vertices method GLPK.glp_java_vertex_get can be used.

For accessing the data areas of arcs and vertices methods GLPK.glp_java_arc_get_data, GLPK.glp_java_vertex_data_get, and GLPK.glp_java_vertex_get_data can be used.

```

glp_arc arc;
glp_java_arc_data adata;
glp_java_vertex_data vdata;

glp_graph graph =
    GLPK.glp_create_graph(
        GLPKConstants.GLP_JAVA_V_SIZE,
        GLPKConstants.GLP_JAVA_A_SIZE);
GLPK.glp_set_graph_name(graph,
    MinimumCostFlow.class.getName());

int ret = GLPK.glp_add_vertices(graph, 9);

GLPK.glp_set_vertex_name(graph, 1, "v1");
GLPK.glp_set_vertex_name(graph, 2, "v2");
GLPK.glp_set_vertex_name(graph, 3, "v3");
GLPK.glp_set_vertex_name(graph, 4, "v4");
GLPK.glp_set_vertex_name(graph, 5, "v5");
GLPK.glp_set_vertex_name(graph, 6, "v6");
GLPK.glp_set_vertex_name(graph, 7, "v7");
GLPK.glp_set_vertex_name(graph, 8, "v8");
GLPK.glp_set_vertex_name(graph, 9, "v9");

vdata = GLPK.glp_java_vertex_data_get(graph, 1);
vdata.setRhs(20);
vdata = GLPK.glp_java_vertex_data_get(graph, 9);
vdata.setRhs(-20);

arc = GLPK.glp_add_arc(graph, 1, 2);
adata = GLPK.glp_java_arc_get_data(arc);
adata.setLow(0); adata.setCap(14); adata.setCost(0);


...
GLPK.glp_write_mincost(graph,
    GLPKConstants.GLP_JAVA_V_RHS,
    GLPKConstants.GLP_JAVA_A_LOW,
    GLPKConstants.GLP_JAVA_A_CAP,
    GLPKConstants.GLP_JAVA_A_COST,
    "mincost.dimacs");
GLPK.glp_delete_graph(graph);

```

6.4 Callbacks

The MIP solver provides a callback functionality. This is used to call method `callback` of class `GlpkCallback`. A Java program can listen to the callbacks by instantiating a class implementing interface `GlpkCallbackListener` and registering the object with method `addListener()` of class `GlpkCallback`. The listener can be deregistered with method `removeListener()`. The listener can use method `GLPK.glp_ios_reason()` to find out why it is called. For details see the GLPK library documentation.

Figure 6.1: Callbacks and Error Handling



6.5 Output listener

GLPK provides a hook for terminal output. A Java program can listen to the callbacks by instantiating a class implementing interface `GlpkTerminalListener` and registering the object with method `addListener` of class `GlpkTerminal`. The listener can be deregistered with method `removeListener()`. After a call to `glp_free_env()` the `GlpkTerminal` has to registered again by calling `GLPK.glp_term_hook(null, null)`. `glp_free_env()` is called if an exception `GlpkException` occurs.

6.6 Aborting a GLPK library call

Method `void GLPK.glp_java_error(String message)` can be used to abort any call to the GLPK library. An exception `GlpkException` will occur. The call must be placed in the same thread as the initial call that is to be aborted. The output method of a `GlpkTerminalListener` can be used for this purpose.

6.7 Debugging support

Method `void GLPK.glp_java_set_msg_lvl(int msg_lvl)` can be used to enable extra output signaling when a GLPK library function is entered or left using value with `GLPKConstants.GLP_JAVA_MSG_LVL_ALL`. The output is disabled by a call with value `GLPKConstants.GLP_JAVA_MSG_LVL_OFF`.

6.8 Locales

Method `void GLPK.glp_java_set_numeric_locale(String locale)` can be used to set the locale for numeric formatting. When importing model files the GLPK library expects to be using locale "C".

6.9 Threads

The GLPK library is not thread safe. Never two threads should be running that access the GLPK library at the same time. When a new thread accesses the library it should call `GLPK.glp_free_env()`. When using an `GlpkTerminalListener` it is necessary to register `GlpkTerminal` again by calling `GLPK.glp_term_hook(null, null)`.

When writing a GUI application it is advisable to use a separate thread for the calls to GLPK. Otherwise the GUI cannot react to events during the call to the GLPK library.

Chapter 7

Examples

Examples are provided in directory examples/java of the source distribution of GLPK for Java.

To compile the examples the classpath must point to glpk-java.jar, e.g.

```
javac -classpath /usr/local/shared/java/glpk-java.jar Example.java
```

To run the examples the classpath must point to glpk-java.jar. The java.library.path must point to the directory with the dynamic link libraries, e.g.

```
java -Djava.library.path=/usr/local/lib/jni \
-classpath /usr/local/shared/java/glpk-java.jar:. \
Example
```

7.1 Lp.java

7.1.1 Description

This example solves a small linear problem and outputs the solution.

7.1.2 Coding

```
import org.gnu.glpk.GLPK;
import org.gnu.glpk.GLPKConstants;
import org.gnu.glpk.GlpkException;
import org.gnu.glpk.SWIGTYPE_p_double;
import org.gnu.glpk.SWIGTYPE_p_int;
import org.gnu.glpk.glp_prob;
import org.gnu.glpk.glp_smcp;

public class Lp {
    // Minimize z = (x1-x2) /2 + (1-(x1-x2)) = -.5 * x1 + .5 * x2 + 1
    //
    // subject to
    // 0.0<= x1 - x2 <= 0.2
    // where,
    // 0.0 <= x1 <= 0.5
```

```

// 0.0 <= x2 <= 0.5

public static void main(String[] arg) {
    glp_prob lp;
    glp_smcp parm;
    SWIGTYPE_p_int ind;
    SWIGTYPE_p_double val;
    int ret;

    try {
        // Create problem
        lp = GLPK.glp_create_prob();
        System.out.println("Problem created");
        GLPK.glp_set_prob_name(lp, "myProblem");

        // Define columns
        GLPK.glp_add_cols(lp, 2);
        GLPK.glp_set_col_name(lp, 1, "x1");
        GLPK.glp_set_col_kind(lp, 1, GLPKConstants.GLP_CV);
        GLPK.glp_set_col_bnds(lp, 1, GLPKConstants.GLP_DB, 0, .5);
        GLPK.glp_set_col_name(lp, 2, "x2");
        GLPK.glp_set_col_kind(lp, 2, GLPKConstants.GLP_CV);
        GLPK.glp_set_col_bnds(lp, 2, GLPKConstants.GLP_DB, 0, .5);

        // Create constraints
        GLPK.glp_add_rows(lp, 1);

        GLPK.glp_set_row_name(lp, 1, "c1");
        GLPK.glp_set_row_bnds(lp, 1, GLPKConstants.GLP_DB, 0, 0.2);
        ind = GLPK.newIntArray(3);
        GLPK.intArray_setitem(ind, 1, 1);
        GLPK.intArray_setitem(ind, 2, 2);
        val = GLPK.newDoubleArray(3);
        GLPK.doubleArray_setitem(val, 1, 1.);
        GLPK.doubleArray_setitem(val, 2, -1.);
        GLPK.glp_set_mat_row(lp, 1, 2, ind, val);
        GLPK.deleteIntArray(ind);
        GLPK.deleteDoubleArray(val);

        // Define objective
        GLPK.glp_set_obj_name(lp, "z");
        GLPK.glp_set_obj_dir(lp, GLPKConstants.GLP_MIN);
        GLPK.glp_set_obj_coef(lp, 0, 1.);
        GLPK.glp_set_obj_coef(lp, 1, -.5);
        GLPK.glp_set_obj_coef(lp, 2, .5);

        // Solve model
        parm = new glp_smcp();
        GLPK.glp_init_smcp(parm);
        ret = GLPK.glp_simplex(lp, parm);

        // Retrieve solution
        if (ret == 0) {

```

```

        write_lp_solution(lp);
    } else {
        System.out.println("The problem could not be solved");
    }

    // Free memory
    GLPK.glp_delete_prob(lp);
} catch (GlpkException ex) {
    ex.printStackTrace();
}
}

/**
 * write simplex solution
 * @param lp problem
 */
static void write_lp_solution(glp_prob lp) {
    int i;
    int n;
    String name;
    double val;

    name = GLPK.glp_get_obj_name(lp);
    val = GLPK.glp_get_obj_val(lp);
    System.out.print(name);
    System.out.print(" = ");
    System.out.println(val);
    n = GLPK.glp_get_num_cols(lp);
    for (i = 1; i <= n; i++) {
        name = GLPK.glp_get_col_name(lp, i);
        val = GLPK.glp_get_col_prim(lp, i);
        System.out.print(name);
        System.out.print(" = ");
        System.out.println(val);
    }
}
}

```

7.2 Gmpl.java

7.2.1 Description

This example reads a GMPL file and executes it. The callback function is used to write an output line when a better MIP solution has been found.

Run the program with the model file as parameter.

```
java -Djava.library.path=/usr/local/lib \
-classpath /usr/local/shared/java/glpk-java.jar:. \
GLPKSwig marbles.mod
```

7.2.2 Coding

```
import org.gnu.glpk.GLPK;
import org.gnu.glpk.GLPKConstants;
import org.gnu.glpk.GlpkCallback;
import org.gnu.glpk.GlpkCallbackListener;
import org.gnu.glpk.glp_iocp;
import org.gnu.glpk.glp_prob;
import org.gnu.glpk.glp_tran;
import org.gnu.glpk.glp_tree;

public class Gmpl implements GlpkCallbackListener {

    public static void main(String[] arg) {
        if (1 != arg.length) {
            System.out.println("Usage:java Gmpl model.mod");
            return;
        }
        new Gmpl().solve(arg);
    }

    public void solve(String[] arg) {
        glp_prob lp = null;
        glp_tran tran;
        glp_iocp iocp;

        String fname;
        int skip = 0;
        int ret;

        GlpkCallback.addListener(this);

        fname = new String(arg[0]);

        lp = GLPK.glp_create_prob();
        System.out.println("Problem created");

        tran = GLPK.glp_mpl_alloc_wksp();
        ret = GLPK.glp_mpl_read_model(tran, fname, skip);
        if (ret != 0) {
            GLPK.glp_mpl_free_wksp(tran);
            GLPK.glp_delete_prob(lp);
            throw new RuntimeException("Model file not found:" + fname);
        }

        // generate model
        GLPK.glp_mpl_generate(tran, null);
        // build model
        GLPK.glp_mpl_build_prob(tran, lp);
        // set solver parameters
        iocp = new glp_iocp();
        GLPK.glp_init_iocp(iocp);
        iocp.setPresolve(GLPKConstants.GLP_ON);
        // solve model
```

```

    ret = GLPK.glp_intopt(lp, iocp);
    // postsolve model
    if (ret == 0) {
        GLPK.glp_mpl_postsolve(tran, lp, GLPKConstants.GLP_MIP);
    }
    // free memory
    GLPK.glp_mpl_free_wksp(tran);
    GLPK.glp_delete_prob(lp);
}

public void callback(glp_tree tree) {
    int reason = GLPK.glp_ios_reason(tree);
    if (reason == GLPKConstants.GLP_IBINGO) {
        System.out.println("Better solution found");
    }
}
}

```

Chapter 8

Troubleshooting

This chapter discusses errors that may occur due to incorrect usage of the GLPK for Java package.

If the GLPK for Java class library was built for another version of GLPK than the GLPK for JNI library a java.lang.UnsatisfiedLinkError may occur in class org.gnu.glpk.GLPKJNI, e.g.

```
Exception in thread "main" java.lang.UnsatisfiedLinkError:  
  org.gnu.glpk.GLPKJNI.GLP_BF_LUF_get()  
  at org.gnu.glpk.GLPKJNI.GLP_BF_LUF_get(Native Method)  
  at org.gnu.glpk.GLPKConstants.<clinit>(GLPKConstants.java:56)
```

If the GLPK for JNI library was built for another version of GLPK than the currently installed GLPK library an java.lang.UnsatisfiedLinkError may occur during dlopen, e.g.

```
Exception in thread "main" java.lang.UnsatisfiedLinkError:  
/usr/local/lib/jni/libglpk_java.36.dylib:  
dlopen(/usr/local/lib/jni/libglpk_java.36.dylib, 1):  
Library not loaded: /usr/local/opt/glpk/lib/libglpk.35.dylib  
Referenced from: /usr/local/lib/jni/libglpk_java.36.dylib  
Reason: image not found  
at java.lang.ClassLoader\$NativeLibrary.load(Native Method)
```

Chapter 9

License

GLPK for Java is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License[1] as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

GLPK for Java is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with GLPK for Java. If not, see <http://www.gnu.org/licenses/>.

Bibliography

- [1] Free Software Foundation, Inc. *GNU General Public License*, 2007.
- [2] Andrew Makhorin. *GNU Linear Programming Kit*. GNU Software Foundation, 2010.
- [3] Sun Microsystems, Inc. *Java Native Interface Specification v1.5*, 2004.
- [4] SWIG.org. *Simplified Wrapper and Interface Generator*, 2010.

Index

abort, 23
callbacks, 21
class path, 16
classes, 16
classpath, 14

debug, 23

examples, 24
exceptions, 19

glp_java_error, 23
glp_java_set_msg_lvl, 23
glp_java_set_numeric_locale, 23
GlpkCallback, 21
GlpkCallbackListener, 21
GlpkException, 19, 23
GlpkTerminal, 23
GlpkTerminalListener, 23

installation, 6
installation path, 8

JNI library, 13, 18

license, 30
Linux, 12, 13
locales, 23

message level, 23

output listener, 23

support, 5
SWIG, 16

threads, 23
troubleshooting, 29

Windows, 12–14